PROLITE LED 1800 DC METRO SPEC

KEY FEATURES

- 1800w LED
- 48 volt DC power
- 0.69 litres p/h
- 140 hours run time
- 9m mast 340° rotate
- 250 hour services
- 3 year LED warranty
- 7 units per semi-trailer

Replaces 4500-6000w halide

Introducing the **Prolite Metro 1800w DC LED tower**, the benchmark for lighting performance and fuel economy.

Versatile. Compact. Reliable and Safe. It's everything you need in a modern, mobile lighting tower.

The most fuel efficient product in its class, Prolite Metro uses just 0.69 litres per hour and runs for 140 hours between refills, reducing your operating costs.

Instant illumination and no cool-down required from four heavy-duty LED panels makes Prolite Metro the perfect tool to light your site.

250 hour service intervals reduce the maintenance workload and a large opening cover provides easy access to the engine bay.

The new Smartgen Series II PLC gives you total control, with programmable timers and key operational data displayed on screen.







TRAILER

- Easy access to all service areas
- Folding drawbar to minimise logistics costs
- Forklift and crane lift-points
- Sound-attenuated cabinet







SPECIFICATIONS

TOWER

Prolite 1800 DC Metro Model

Engine Hatz 1B30

Sincro FB4-48/100 Alternator

48v DC Main voltage

LIGHTS

No. of Lights 4 x LED 1800W Lighting Power 189,000 Lumens Life of Globe 50,000 hours

NOISE

Sound Level 73.08dB(A) at 1m 67.77dB(A) at 7m Sound Level

MAST

9 Metres (Extended) Height of Mast

Rotation 340 degree Wind Rating 110km/hr

FUEL

Fuel Consumption 0.69 Litres/Hour 140 Hours **Running Time** Fuel Tank Capacity 100 Litres

TRAILER DIMENSIONS

2200 mm Length Weight (wet) 1185 kg Width 1800 mm Tow hitch 50mm ball 2198 mm Wheel size 13" Height

OPTIONAL EQUIPMENT

GPS tracking LED beacon







